



reddot award 2017  
winner



## shot Design: Sebastian David Büscher

für festen Untergrund

for solid ground

**Lichttechnik:**  
230V Power LED  
IvyLight-technology  
3000K warmweiß  
L70/50.000 h

**Flood Reflektor** symmetrisch  
dimmbar

**Anschluss:**  
5 m Zuleitung  
(H05RN-F 3G0,75) inkl. Schutz-  
kontaktstecker anschlussfertig

ortsveränderlich

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Sicherheitsglas klar  
  
inkl. Alu-Ring lose, ø 80 mm

**Schutzart:**  
IP65

**EEK:**  
A+

light technology:  
230V Power LED  
IvyLight-technology  
3000K warm white  
L70/50.000 h

flood reflector symmetric  
dimmable

connection:  
5 m supply cable  
(H05RN-F 3G0,75 ) incl. safety  
plug ready to connect

movable


material:  
aluminium die-casting  
powder-coated  
safety glass clear

incl. aluminium ring loose, ø80 mm

protection class:  
IP65

**EEC:**  
A+

### shot 4 W



Größe in mm  
size in mm

**Art.-Nr.**  
item no.

**Farbe**  
colour

**Systemleistung**  
system performance

**Lichtrichtung**  
light direction

91090-4W-AN

anthracite  
RAL 7016

4 W/260 lm




91090-4W-CB

cool brown

4 W/260 lm



### shot 15 W



Größe in mm  
size in mm

91090-15W-AN

anthracite  
RAL 7016

15 W/980 lm



91090-15W-CB

cool brown

15 W/980 lm



+ Anschluss optional mit IP44.de connect. Produktdetails on [www.IP44.de](http://www.IP44.de).  
connection with IP44.de connect as an option. product details on [www.IP44.de](http://www.IP44.de).

#### IP44.de outside lighting

Mühlenstraße 20 . 33378 Rheda-Wiedenbrück . Germany  
T +49 5242 5797-0 . F +49 5242 5797-10  
[welcome@IP44.de](mailto:welcome@IP44.de) . [www.IP44.de](http://www.IP44.de)

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.  
IP44.de reserves the right to product adaptations at any time, without prior notice.